



**PREVENTATIVE
MAINTENANCE SOLUTIONS**

CLEANER APPLICATION TOOL

MODEL #72450

KEY FEATURES:

- **WORKS OFF SHOP AIR, NO AEROSOL CANS REQUIRED**
- **THE ABILITY TO PRESSURE-CHECK THE FUEL-SYSTEM**
- **A PRESSURE-RELEASE BUTTON AND QUICK-SHUT-OFF VALVE FOR SAFETY • A PRESSURE REGULATOR FOR ACCURATE USE**
- **CONNECTS DIRECTLY TO THE VEHICLE'S FUEL-RAIL OR THROTTLE-BODY USING AN ASSORTMENT OF ADAPTORS**
- **STAINLESS STEEL FITTINGS AND CONNECTORS FOR DURABILITY AND PRODUCT COMPATIBILITY • COMPLETE SET OF FUEL-RAIL ADAPTORS ARE AVAILABLE**
- **A "FLUID-FLOW" SIGHT GLASS • A UNIQUE SEE-THROUGH HOUSING, SO PRODUCT USAGE CAN BE MONITORED**
- **A 24-OUNCE FLUID CAPACITY FOR COMBINED-PRODUCT APPLICATIONS**

MOC®'s Cleaner Application Tool Allows The Technician to Perform an "On Engine" Cleaning of The Entire Fuel-System.

OVERVIEW: Today's vehicles have more sophisticated fuel inductions systems due to modern design and increased performance requirements. Accordingly, fuel-system deposits can greatly affect engine performance and cause driveability problems. However, traditional methods of replacing or manually cleaning fuel-system components can be costly, ineffective and time-consuming. The fast, effective alternative to remove deposits and improve driveability is to introduce one of **MOC®'s premium cleaners** into the fuel system using the **Cleaner Application Tool**. This versatile apparatus can remove deposits from the entire fuel-system, including injectors, combustion chambers and air intake depending on the product and adaptors used with it.

THE SERVICE: To start the process, cleaner is added to the large-capacity canister through a convenient funnel-shaped fill area. Once the cap is in place, shop air is attached to pressurize the tool. The steel-braided outlet hose can be attached to the fuel-rail or throttle-body through various adaptors. An air regulator and intake valve control the flow rate of product into the system. Next, a "Fluid-Flow" sight glass allows the technician to monitor usage and indicates when the service is finished. Also included is a fuel bypass hose, for vehicles equipped with return-less fuel systems.



SPECIFICATIONS:

Dimensions:	18" H x 6" W x 6" D
Weight (dry):	4.02 lbs.
Power:	Compressed Air
Tank Material:	6061-T6 Aluminum
Service Hoses:	51 inches
Limited Warranty:	6 months, parts

