

COOLING-SYSTEM FAST FLUSH

AUTOMOTIVE ADDITIVES & LUBRICANTS - #0109



OUTSTANDING FEATURES

- Non-acid.
- Requires no neutralizer.
- Highly effective at removing scale and sediment from system surfaces.
- Can be used on radiator plastic and aluminum components.

DESCRIPTION

A powerful, convenient, one-step radiator and cooling-system cleaner. It is formulated to quickly breakdown and suspend rust, scale, and sediment. This non-acid-base product needs no neutralizer and is compatible with plastic and aluminum.

APPLICATION

Allow system to cool before removing radiator cap. 1) Remove radiator cap. 2) Pour Fast Flush into radiator. 3) Replace radiator cap. 4) Run engine at operating temperature for ten to fifteen minutes. 5) Flush system with a MOC® Coolant Exchanger Machine. Refer to the machine's instructions for additional details and information.

SPECIFICATIONS

<u>Test</u>	<u>ASTM Method</u>	<u>Typical Results</u>
Appearance	-	Clear & Bright
Color	-	Colorless to pale yellow
Odor	-	Mild
pH	-	7-7.5
Density (g/mL)	D4052	1.06
'Density, U.S. (lbs/gal), calculated	-	8.87
Boiling Point(°F)	-	>212

PACKAGING

Fill: 8 oz.

Case Quantity: 24

Case Weight: 16 lbs.