

COOLING-SYSTEM TREATMENT

AUTOMOTIVE ADDITIVES & LUBRICANTS - #0111



OUTSTANDING FEATURES

- Compatible with all types of coolant (conventional - green, extended life - Dex-Cool, Hybrid - GO-5, Asian and European formulas). Based on ASTM D4334 test results.
- Proven to increase corrosion inhibiting performance of treated coolant and fortify system surfaces from corrosion damage for an extended period. Based on ASTM D3306 test results.
- Increases protection of water pump and reduces potential damage to pump surfaces. Based on ASTM D2809 test results.

DESCRIPTION

A universal formula that is compatible with all types of coolant-antifreeze. This product contains a unique corrosion and rust inhibitor technology that enhances protection of cooling system metals such as iron, aluminum, copper, and solder. It contains anti-foaming agents and provides additional protection to water pumps.

APPLICATION

Add one bottle of MOC® Cooling System Treatment to the cooling system any time a service is performed, or additional rust and corrosion protection is desired.

SPECIFICATIONS

| <u>Test</u> | <u>ASTM Method</u> | <u>Typical Results</u> |
|-------------------------------------|--------------------|------------------------|
| Appearance | - | Clear & Bright |
| Color | - | Yellow -Brown |
| Odor | - | Faint Ammonia |
| pH | D1287 | 8.7-9.5 |
| Density (g/ml) | D4052 | 1.06 |
| Density, U.S. (lbs/gal) calculated | - | 8.85 |
| Boiling Point(°F) | - | >212 |
| Flash Point(°F) based on components | - | >232 |

PACKAGING

Fill: 8 oz.

Case Quantity: 24

Case Weight: 16 lbs.

