

POWER STEERING SERVICE SOLUTION

AUTOMOTIVE ADDITIVES & LUBRICANTS - #0123



OUTSTANDING FEATURES

- Reduces friction and heat that can wear out the pump, valves and gears.
- Enhanced resistance to breakdown due to shearing and system pressure.
- Conditions seals and hoses to help prevent cracks and leaks.
- Helps extend system life by reducing wear on internal components.
- Helps reduce squeals and chatter due to foaming.
- Outstanding cold weather performance.

DESCRIPTION

A fortified power-steering fluid blend that is used in conjunction with a MOC® Power-Steering Fluid Exchanger. This product contains a special additive package for enhanced shear stability, anti-wear and thermal stability. It is suitable for use in Ford®, GM®, Chrysler®, and many other types of vehicles. Important:

This fluid is NOT suitable for use in Honda®/Acura® vehicles.

APPLICATION

MOC® Power-Steering Service Solution #01231 should only be used with a MOC® Power-Steering Fluid Exchanger.

1. Follow the MOC® Power-Steering Fluid Exchanger instructions to perform the exchange process. 2. Dispose of used fluid in accordance with local, state and federal regulations.

SPECIFICATIONS

<u>Test</u>	<u>ASTM Method</u>	<u>Typical Results</u>
Appearance	-	Clear
Color	-	Light Amber
Odor	-	Bland
Density (g/mL)	D4052	0.85
Density, U.S. (lbs/gal), calculated	-	7.07
Viscosity,cSt @ 100°C	D445	~7.4
Viscosity,cSt @ 40°C	D445	~36
Viscosity Index	D2270	~180
Boiling Point(°F)	-	>487
Flash Point(°F)(based on components)	-	>248

PACKAGING

Fill: 64 oz.

Case Quantity: 4

Case Weight: 17 lbs.