

GEAR GUARD™ PLUS SAE 75W-85

AUTOMOTIVE ADDITIVES & LUBRICANTS - #0147



OUTSTANDING FEATURES

- Superior lubrication and protection for bearings and gears.
- Helps prevent wear, pitting, gear noise and corrosion under high-load conditions.
- Excellent fluidity and protection in extreme temperatures.
- Contains special additives to reduce chattering in limited-slip differentials.
- Meets stringent industry standards, including API GL-5, MT-1, MILL 2105 D-E, 2105E and SAE J2360 specifications.

DESCRIPTION

A multigrade synthetic (polyalphaolefin), A.P.I. GL-5 rated gear oil formulated to SAE 75W-85 viscosity. It is a premium extreme-pressure lubricant designed for use in axle applications requiring limited-slip performance but can also be used in conventional differentials. **MOC® Gear Guard™ Plus SAE 75W-85** is a versatile product that can be used in place of **SAE 75W, SAE 80, SAE 85** oils and eliminates the need for a supplemental friction modifier. It is designed to provide excellent extreme pressure protection, load carrying capacity, anti-foam performance, corrosion protection, and thermal stability protection.

APPLICATION

Follow vehicle manufacturer's recommendations for use of product. Gear Guard™ Plus is designed to be used in conjunction with MOC® Differential/Driveline service equipment and tools.

SPECIFICATIONS

Test	ASTM Method	Typical Results
Appearance	-	Oil
Color	-	Amber
Odor	-	Petroleum
Density (g/mL) @68 °F	D4052	0.85
Density, U.S. (lbs/gal), calculated @68 °F	-	7.09
Viscosity @ 100°C, cSt	D445	13.5-18.5
Viscosity @ 40°C, cSt	D445	~120
Brookfield Viscosity @ -40° C, cP	D2983	<150,000

PACKAGING

Fill: 1 quart

Case Quantity: 12 Bottles

Case Weight: 24.14 lbs.