



LIMITED-SLIP CONCENTRATE

AUTOMOTIVE ADDITIVES & LUBRICANTS - #0149

OUTSTANDING FEATURES

- Enhances limited-slip performance (anti-chatter) of rear axles.
- Compatible with most conventional and synthetic gear oils.
- Eliminates the need for inventory multiple gear oils.

DESCRIPTION

Designed to prevent chatter in limited-slip differentials and full-time four-wheel drive transfer cases. This product helps quiet gears in the differential and fortify standard gear lubricants. It is designed to be used with any GL-5 gear lubricant in limited-slip applications. Recommended for rear-wheel drive passenger cars, trucks, and sport utility vehicles.

APPLICATION

Add 1-part concentrate to every 25 parts of gear lubricant. Add treated gear lubricant to vehicle. Do not overfill system. For best results, use MOC® Limited-Slip Concentrate with MOC® Gear Guard™ #0148 or #0414 gear oil. Product may be added between services or as needed.

SPECIFICATIONS

<u>Test</u>	<u>ASTM Method</u>	<u>Typical Results</u>
Appearance	-	Clear & Bright
Color	-	Amber
Odor	-	Petroleum
Density (g/mL)	D4052	.91
Density, U.S. (lbs/gal), calculated	-	7.60
Viscosity, cSt @ 100°C	D445	~7
Viscosity, cSt @ 40°C	D445	~46
Flash Point(°F), PMCC	D93	≥257

PAKAGING

Fill: 4 oz.

Case Quantity: 12

Case Weight: 3 lbs.

