

MULTI-VEHICLE SYNTHETIC ATF

AUTOMOTIVE ADDITIVES & LUBRICANTS - #0411



OUTSTANDING FEATURES

- Full synthetic formula; not a synthetic blend.
- Highly resistant to shearing, oxidation and thermal breakdown.
- Provides excellent flow properties at low temperatures and film protection at high temperatures.
- Outstanding anti-wear properties to protect transmission parts.
- Optimizes Inventory by eliminating the need to stock different types/brands of ATF.
- Conditions seals and helps prevent leaks.

DESCRIPTION

A special blend of fully synthetic base oils combined with a multi-functional additive system that provides superior anti-wear protection and performance in virtually all types of passenger and commercial automatic transmissions. It offers excellent high & low temperature fluidity, shear stability, seal protection and oxidation resistance. This premium formula may be used in place of synthetic fluids required or specified by a wide range of OEMs, including those used for extended drain and severe duty intervals. This product is designed to be used in conjunction with the **MOC® ATF Fluid Exchanger #94500 & ATF Cleaner/Supplement Kit #01941..**

APPLICATION

Use in automatic transmissions according to equipment manufacturer's recommendations. **DO NOT** use in transmissions that require CVT or Type F fluids.

SPECIFICATIONS

Test	ASTM Method	Typical Results
Appearance	-	Clear
Color	-	Red
Density (g/mL)	D4052	0.85
Density, U.S. (lbs/gal), calculated	-	7.09
Viscosity, cSt @ 40°C	D445	~38
Viscosity, cSt @ 100°C	D445	~7.00
Viscosity Index	-	147
Brookfield Viscosity @ -40°C, cP	-	~13,000
Pour Point °C	D97	-40
Flash Point °F		419

PACKAGING

Fill: 1 gal	Case Quantity: 4	Case Weight: 30 lbs.
Fill: 3 gal	Case Quantity: 2	Case Weight: 46 lbs.
Fill: 55 gal	Case Quantity: 1 Drum	Case Weight: 415 lbs.