

GEAR GUARD™

SAE 75W-90

AUTOMOTIVE ADDITIVES & LUBRICANTS - #0414



OUTSTANDING FEATURES

- Superior lubrication and protection for bearings and gears.
- Helps prevent wear, pitting and corrosion under high-load conditions. Helps reduce gear noise and increases driveline efficiency.
- Meets stringent industry standards including A.P.I. GL-5, MT-1 and SAE J2360 specifications.

DESCRIPTION

A synthetic Polyalphaolefin, A.P.I. GL-5 rated gear oil formulated to SAE 75W-90 viscosity. It is a versatile extreme-pressure lubricant designed for use in conventional differentials, limited-slip differentials, and manual transmissions. MOC® Gear Guard™ SAE 75W-90 can be used in place of SAE 75W, SAE 75W-85, SAE 80, SAE 80W-90, or SAE 90 in a wide range of domestic and foreign vehicles.

APPLICATION

Follow vehicle manufacturer's recommendations for use of product. Gear Guard™ is designed to be used in conjunction with MOC® Differential / Driveline service and tools. NOTE: Limited-slip differentials require the use of MOC® Limited-Slip Concentrate #0149 with MOC® Gear Guard™.

SPECIFICATIONS

<u>Test</u>	<u>ASTM Method</u>	<u>Typical Results</u>
Appearance	-	Clear & Bright
Color	-	Yellow
Odor	-	Sulfur
Density (g/mL)	D4052	0.84
Density, U.S. (lbs/gal), calculated	-	7.10
Viscosity @ 100°C, cSt	D445	14.0
Viscosity, cSt @ 40°C	D445	60
Flash Point °F (based on components)	-	>230
Brookfield Viscosity @ -40°C, cP	D2983	<100,000

PACKAGING

Fill: 1 qt.	Case Quantity: 12	Case Weight: 24 lbs.
Fill: 16 gal.	Case Quantity: 2	Case Weight: 248 lbs.