



MTF

MANUAL TRANSMISSION FLUID

AUTOMOTIVE ADDITIVES & LUBRICANTS - #0429

KEY FEATURES

- Maintains fluidity at low temperatures.
- Prevents rust and fluid oxidation.
- Compatible with components containing copper.
- Extended service life.
- Excellent film protection at high temperatures.

DESCRIPTION

A full synthetic, SAE 75W-90 GL-4 gear oil for use in a wide range of manual transmissions and transaxles requiring a GL-4 lubricant. It contains a premium multi-functional additive package with high-quality base stock that provide excellent low temperature fluidity, extreme pressure performance and high temperature protection. Special inhibitors and additives are included to provide compatibility with copper containing alloys and protect against corrosion. It can be used in applications that call for General Motors Part# 12345371.

APPLICATION

Use quantity in accordance with vehicle manufacturer's recommendations.

SPECIFICATIONS

Test	ASTM Method	Typical Results
Appearance	-	Clear
Color	-	Yellow
Odor	-	Sulfur
Specific Gravity @ 68°F	D1298	0.84
Density, U.S. (lbs/gal) @ 68°F	D1250	7.01
Viscosity @ 100°C, cSt	D445	14.8
Viscosity, cSt @ 40°C	D445	65.6
Viscosity Index	D2270	238
Brookfield Viscosity @ -40°C, cP	D2983	~27,000

PACKAGING

Fill: 32 OZ.

Case Quantity: 12

Case Weight: 24 lbs.