



# PROTECT

## ADVANCED COOLING SYSTEM PROTECTION

AUTOMOTIVE ADDITIVES & LUBRICANTS - #0444

### OUTSTANDING FEATURES

- Compatible with all types of coolant when used in indirect cooling systems.
- Fortifies and extends service life of new coolant
- Lowers metal loss to less than 1 mg
- Can help regulate EV Battery Temperatures

### DESCRIPTION

Designed to fortify coolants used in hybrid-electrical vehicles (HEV) and battery electrical vehicles (BEV) with advanced corrosion inhibitors. It is formulated for use in all types of ethylene glycol based, low-conductivity coolants used in indirect cooling systems.

### APPLICATION

**SHAKE WELL!** If used between services, allow cooling system to cool before removing radiator or reservoir cap to add product. **1)** Remove radiator or reservoir cap and add entire contents of container to cooling system. **2)** Replace radiator or reservoir cap & allow car to idle for 10-15 minutes.

### SPECIFICATIONS

<u>Test</u>	<u>ASTM Method</u>	<u>Typical Results</u>
Appearance	-	Clear & Bright
Color	-	Yellow
Odor	-	Neutral
pH	D1287	9.5
Specific Gravity @ 68°F	-	1.07
Density, U.S. (lbs/gal) @ 68°F	-	8.97
Boiling Point(°F)	-	>212
Flash Point(°F)(based on components)	-	>232

### PACKAGING

**Fill:** 10 oz.

**Case Quantity:** 24

**Case Weight:** 20 lbs.