

HEAVY-DUTY DOT 3 BRAKE FLUID

AUTOMOTIVE ADDITIVES & LUBRICANTS - #0600



OUTSTANDING FEATURES

- High-boiling point formula (ERBP of ~485°F).
- Exceeds DOT specifications for DOT 3 brake fluid (DOT minimum is 404°F).
- Two convenient sizes for use with fluid exchange equipment.
- Excellent high-temperature protection and moisture resistance.

DESCRIPTION

A high quality product which meets and exceeds the DOT specifications for DOT 3 brake fluid.

APPLICATION

This product is to be used with a #98000 MOC® Pure Brake™ Brake-Fluid Exchanger. Follow directions in the machine's instruction manual for use of this product.

SPECIFICATIONS

Test	ASTM Method	Typical Results
Appearance	-	Clear & Bright
Color	-	Light Straw
Odor	-	Slight Ethereal
Specific Gravity @ 68°F	ASTM D4052	1.04
Density, U.S. (lbs/gal) (Calculated)	-	8.7
Viscosity, cSt @ -40°C	ASTM D445	1,160
Dry ERBP, °F	SAE J-1703	~485
% Water	ASTM D1209	<0.3

PACKAGING

Fill: 32 oz.	Case Quantity: 12 Bottles	Case Weight: 28.8 lbs.
Fill: 53 oz.	Case Quantity: 4 Bottles	Case Weight: 15.95 lbs.