

# ULTRA DOT 4-LV BRAKE FLUID

AUTOMOTIVE ADDITIVES & LUBRICANTS - #0603



## OUTSTANDING FEATURES

- Low viscosity formulation, faster response at lower temperatures.
- High-boiling point formula (ERBP of ~265 °C / 509 °F).
- Wet boiling point (ERBP of ~170 °C / 338°F).
- Ideal for use in vehicles with ESC and ABS brake systems
- Resists moisture absorption and retention.
- Do not mix with DOT 5 Silicone-Based brake fluid

## DESCRIPTION

A premium, low viscosity brake fluid recommended for use in vehicles fitted with ESC (Electronic Stability Control), ABS (Anti-lock Braking System) and ASR (Acceleration Slip Regulation). Ultra DOT 4 LV is fully tested and certified to meet or exceed technical standards including: FMVSS 116, SAE J1704 and ISO 4925 Class 6.

**IMPORTANT: Do not mix with DOT 5 Silicone-Based Brake Fluid**

## APPLICATION

This product is to be used with a #98000 MOC® Pure Brake™ Brake-Fluid Exchanger. Follow directions in the machine's instruction manual for use of this product.

## SPECIFICATIONS

Test	Test Method	Typical Results
Appearance	-	Clear & Bright
Color	-	Pale Yellow
Odor	-	Mild
Specific Gravity @ 68°F	ASTM D4052	~1.05
Density, U.S. (lbs/gal) (Calculated)	-	~8.76
Kinematic Viscosity, cSt@ -40°C	FMVSS 116	~549
Kinematic Viscosity, cSt@ 100°C	FMVSS 116	~1.9
Dry ERBP, °F	FMVSS 116	~504
Wet ERBP, °F	FMVSS 116	~336

## PACKAGING

**Fill:** 32 oz.

**Case Quantity:** 12 Bottles

**Case Weight:** 29.6 lbs.

