

POWER STEERING FLUSH SOLUTION

AUTOMOTIVE ADDITIVES & LUBRICANTS - #0604



OUTSTANDING FEATURES

- Reduces friction and heat that can wear out the pump, valves, and gears.
- Enhanced resistance to breakdown due to shearing and system pressure.
- Conditions seals and hoses to help prevent cracks and leaks.
- Extends system life by reducing wear on internal components.

DESCRIPTION

Designed to remove harmful system deposits and impurities. Use it prior to one of the MOC® Power-Steering Service Solutions to help remove depleted fluid and contaminants. Use only in conjunction with a MOC® Power-Steering Fluid Exchanger.

APPLICATION

Follow the MOC® Power-Steering Fluid Exchanger instructions to perform the exchange process. Dispose of used fluid in accordance with local, state and federal regulations. MOC® Power-Steering Flush Solution #0604 should only be used with a MOC® Power-Steering Fluid Exchanger.

SPECIFICATIONS

<u>Test</u>	<u>ASTM Method</u>	<u>Typical Results</u>
Appearance	-	Clear
Color	-	Amber
Odor	-	Mild Petroleum
Specific Gravity @ 68°F	D1298	0.85
Density, U.S. (lbs/gal) @ 68°F	D1250	7.1
Viscosity cSt @ 100°C	D445	~7
Viscosity cSt @ 40°C	D445	~35
Viscosity Index	D2270	~200
Brookfield Viscosity cP @ -40°C	D2983	~13,000
Boiling Point (°F)	-	≥ 599
Flash Point (°F) (based on components)	-	≥ 248

PACKAGING

Fill: 64 oz

Case Quantity: 4 Bottles

Case Weight: 17 lbs.

