

# PREMIUM SYNTHETIC ATF - RED

AUTOMOTIVE ADDITIVES & LUBRICANTS - #0611



## OUTSTANDING FEATURES

- Superior oxidation stability.
- Very good cold weather performance.
- Improved shear stability.
- Conditions seals and hoses.

## DESCRIPTION

Formulated to provide wear and rust protection, lubricity, good flow properties, excellent high and low temperature performance as well as stringent anti-shudder capability. This fluid is suitable for use in Ford, General Motors, Chrysler ATF+4, Allison C4, Volkswagen #G052 162A2, Audi, Volvo, Toyota (T-IV), Lexus, Honda Z1, Hyundai, Nissan (Matic-J), Infiniti, BMW, Mercedes Benz, and Jaguar.

## APPLICATION

MOC® Premium Synthetic ATF (#0611) must be used according to equipment manufacturer's recommendations. Do not use in transmissions which require CVT or Dexron VI fluid.

## SPECIFICATIONS

<u>Test</u>	<u>ASTM Method</u>	<u>Typical Results</u>
Appearance	-	Oil
Color	-	Red
Odor	-	Petroleum
Specific Gravity @ 68°F	D1298	0.85
Density, U.S. (lbs/gal) (Calculated)	-	7.1
Viscosity, cSt @ 100°C	D445	7
Viscosity, cSt @ 40°C	D445	30
Viscosity Index	D 2270	> 170
Phosphorus Content, ppm (calculated)	-	180

## PACKAGING

**Fill:** 1 gal.  
**Fill:** 3 gal.

**Case Quantity:** 4 Bottles  
**Case Quantity:** 2 Bottles

**Case Weight:** 30 lbs.  
**Case Weight:** 46 lbs.

# ATF COMPATIBILITY CHART



## MULTI-VEHICLE SYNTHETIC ATF FLUID

A special blend of fully-synthetic base oils, combined with a multi-functional additive system that provides superior anti-wear protection and performance in virtually all types of passenger and commercial automatic transmissions. It offers excellent high & low temperature fluidity, shear stability, seal protection and oxidation resistance. Part # 0611X (AVAILABLE SIZES - 1 GAL, 3 GAL)

OEM	TRANS / PN
ACURA	ATF-Z1, TYPE 2.0 PN 082009015A, PN 08200-9017A
AISIN WARNER	JWS 3309 (TIV) & JWS 3324 (WS), AS69RC, 05189966AB, 05189977AA
ALFA ROMEO	ALL
ALLISON	C-3, C-4, John Deere HD SynTran™, Mobil Delvac Synthetic ATF™, TES 668
AMERICAN MOTORS	ALL
ASTON MARTIN	ALL
AUDI	G052025A2, G052162 A1/A2, LT71141, G055025A2, G052990A2, G055540A2
BENTLEY	ALL INCLUDING PY112995PA
BMW	LA2634, LT71141, 81229400275, 83220142156, 83220403248, 83229407765, 83229407807, 83220026922, BMW807, BMW 7045E, ZF 5HP18FL, 5HP24, 5HP30, TEXACO ETL-7045E, TEXACO ETL-8072B, 705/ATFD-3, 83220402413, 83227542290
CATERPILLAR	T0-2
CHRYSLER / MOPAR	ATF 7176, +2, +3 (MS-7176E), +4 (MS-9602), AS68RC, AS69RC, 05127382AB, 05189966AB, 05189966AA, 05189977AA, 05127382AA, JWS3309, 68043742AA, 68089195AA
CITROEN	973622, Z000169756
DAEWOO	ALL INCLUDING, LT71141
DIWA / DAIHATSU	AMMIX ATF D-II, AMMIX ATF D-III SP
ESSO	ATF LT 71141
FIAT-LANCIA	ALL
FORD	MERCON® (XT-2-QDR OR XT-2-QSM), MERCON®SP (XT-6-QSP), MERCON®V (XT-5-QM), PREMIUM AUTOMATIC TRANSMISSION FLUID (XT-8-QAW), FNRS AUTOMATIC TRANSMISSION FLUID (XT-9-QMM5), X-2-QDX, M2C138CJ, M2C166H WSS M2C 922A1, 924A (XT-8-QAW) JWS 3309
FUCHS / FUSO	Titan ATF 3292, Titan ATF 3353 / ATF- II, ATF-SP III, AFT-A4
GENERAL MOTORS	DEXRON®, DEXRON®-II, -IID, -IIE, -III, -IIIG/H, GM TIV (PN 88900925), AW1, 9986195 (Aisin AW, JWS 3309)
HONDA	ATF-Z1 (EXCEPT CVT), 08200-9017, 08200-9015
HYUNDAI	SP-II/DEX-II, SP-III, 00232-19012, 00232-19015, 00232-19016, 00232-19023 / 24, JWS-3309 T-4, JWS 3314 00232-19057, 00232-19059, NWS 9683
IDEMITSU	K17, JATCO 3100 PL085, W0133-19031-54
INFINITI	ALL INCLUDING MATIC D, J, K
ISUZU	BESCO ATF-II, ATF-III, ATF SP, SCS Fluid
JAGUAR	ATF 3403 M115, ATF 3403, C2C8432, ZF 5HP24, 1X43 2C9010AA, JLM 20237, JLM 20238, LT71141, JATCO 3100 PL085, JDE 26444

MOC® does not recommend Premium Synthetic ATF - LV for use in the following applications: Continuously Variable Transmissions (CVT), Dual Clutch Transmissions (DCT), Direct-Shift Gearbox (DSG), FORD - (Type F, MERCON® ULV & XT-12-QULV), & GM (DEXRON®-HP). In addition, the vehicle manufacturers listed above have neither evaluated nor endorsed Multi-Vehicle Synthetic ATF. Always follow equipment manufacturers' recommendations for use in automatic transmissions.

# ATF COMPATIBILITY CHART CONTINUED



**PREVENTATIVE  
MAINTENANCE SOLUTIONS**



OEM	TRANS / PN
JASO	M315-2013 1A, 2A
JEEP	ATF 7176, +2, +3 (MS-7176E), +4 (MS-9602), AS68RC, AS69RC, 05127382AB, 05189966AB, 05189966AA, 05189977AA, 05127382AA, 68157995AA, 68157995AB, 68218925AA, 68171866, 68171869AB
JWS	3309, 3314, 3317
KIA	SP-II, SP-III, RED 1, ATF TYPE 4(M)
LAND ROVER	ESSO LT71141, TEXACO N402, LRN 13754, TEXACO ETL-7045E, STC4863, STC 505.31, LR 002748
LEXUS	ATF D-II, ATF D-III, TYPE T, T-II, T-III, TYPE T-IV
MAN	339F, 339V1, 339V2, 339Z1, 339Z2, 339Z3
MAZDA	ATF D-II, ATF-M III, ATF-MV, ATF-FZ, ATF F-1, ATF S-1, ATF N-1, ATF 3317, 0000-77-112E-01, 0000-77-120E-05, 0000-77-114E-01, 0000-FZ-113E-01
MERCEDES BENZ	236.1, 236.2, 236.3, 236.5, 236.6, 236.7, 236.8, 236.9, 236.10, 236.11, 236.81, 0019892103, SHELL 3403-4 115, A0019892203, 0019894503, ATF 4134, 0019896803
MASERATI	231603
MATRA	ALL
MITSUBISHI	DIAQUEEN SK, SP, SP-II, SP-III, AW, J2,
NISSAN	MATIC C, D, J, K, 402
OPEL	ALL
PEUGEOT	ZF 4HP20, 973622, Z000169756
PORSCHE	ZF 5HP19FL, ZF 5HP20, LT71141 ATF 3403-M115, FIV (JWS 3309), 99991754700A2, 00004320509, 00004320441, SHELL 3403 M115, 99991754700, 000 043 205 28
RENAULT 7	Samsung SATF-D, 711218368
ROLLS ROYCE	PL31493 PA
SAAB	T-IV, 93160372, 93160393, 93165147
SATURN	AW1, 88863400, 88863401, 22689186, ALL
SHELL	LA2634, ATF 3353, ATF 3403, M115, M-1375.5
SUBARU	DEXRON®-II, ATF 5AT, SOA868V9241, KO140Y0700, ATF-HP, HP/PS (SOA427V1500 HP), ALL
SUZUKI	99980-06000, ATF 3317 SP-4B, 990B0B-01001, ATF 3314, AT OIL 5D06, ATF 2326, ATF 2384K, JWS 3309
TEXACO	ETL-7045E, ETL-8072B, N402
TOYOTA	ATF D-II, ATF D-III, TYPE T, T-II, T-III, TYPE T-IV
VOITH	55.6335.XX (G607), 55.6336.XX (G1363)
VOLVO	97340, 97341, 97342, 3344208, 31256776, 1161521, 1161540, 1161640, 1161621, CE 97340
VOLKSWAGEN	G055025A2, G052162A2, G052990A2, G052025A2, G052162A1, LT71141, G055540A2, 5 HP (ZF 5 HP 30) (18FL, 30) (19FL, 24A)
ZF FRIEDRICHSHAFEN	AG TE-ML: 02F, 03D, 04D, 05L, 09, 11A, 11B, 14A, 14B, 14C, 16L, 17C, 20B; SHELLLA 2634, LT 71141, LifeGuard Fluid 9

MOC® does not recommend Premium Synthetic ATF - LV for use in the following applications: Continuously Variable Transmissions (CVT), Dual Clutch Transmissions (DCT), Direct-Shift Gearbox (DSG), FORD - (Type F, MERCON® ULV & XT-12-QULV), & GM (DEXRON®-HP). In addition, the vehicle manufactures listed above have neither evaluated nor endorsed Multi-Vehicle Synthetic ATF. Always follow equipment manufacturers' recommendations for use in automatic transmissions.