Product Performance & Data Sheet

Product Name

Product Part

Product Category

Silicone Lubricant

1003

Aerosols

ZIICONE

OTECTS - LUBRICATES - PRESERVE

Description:

MOC® Silicone Lubricant #1003 is a multipurpose, liquid lubricant. It was formulated to provide a clean, non-greasy, lubricating film. This product provides excellent "slide-and-glide" properties which reduces binding and squeaks caused by friction. It prevents bonding or build-up of paint, wax, ink, and adhesives on treated surfaces. Also, this product will seal out moisture to help prevent rust and corrosion on metal surfaces. MOC® Silicone Lubricant may be applied to metal, rubber, plastic, nylon, wood and vinyl. Typical applications are glass installation, windshield wiper assemblies, rubber molding, belts, hinges, slides, springs and latches

Outstanding Features:

- No greasy residue provides a non-staining, lubricating film.
- Reduces friction has excellent "slide-and-glide" properties.
- Creates a barrier to prevent bonding or build-up of wax, ink, paint and adhesives on treated surfaces.
- Rustproof protects metal surfaces from rust and corrosion.
- Repels water and seals out moisture.
- Versatile may be used on rubber, plastic, nylon, vinyl, wood, and metal to prevent binding, sticking and deterioration.
- Low V.O.C. formula.

L

Application:

Shake can well before using. Holding can 4 to 8 inches from surface, spray area. Use extension tube for hard-to-reach areas.

Specifications:

Test	ASTM Method	Typical Results
Appearance	-	Clear Liquid
Color (liquid portion)	-	Colorless to Pale Yellow
Odor	-	Solvent
Specific Gravity @ 60°F	D1298	0.75
Density, U.S. (lbs/gal) @ 60°F	D1250	6.26
Flammability, NFPA 30B	-	Level 3 Aerosol

Packaging: Fill: 10 oz. Case Quantity: 12 cans Case Weight: 14 lbs.

