

MEDIUM-DUTY COMPOUND

AUTOMOTIVE BUFFING COMPOUND - #3111

PERFORMANCE RATING - Abrasiveness - 8

OUTSTANDING FEATURES

- Dries slowly, great "open" time, even with a high-speed buffer.
- Easily "spurred" from the pad for quick clean-up.
- Accidental "sling" can be easily removed with a dry cloth.
- Generates very little powder and easily wipes clean.



DESCRIPTION

A semi-viscous, light brown, lotion type compound that can be used on conventional paints to remove scratches and light oxidation.

APPLICATION

Pour **Medium-Duty Liquid Compound** into dispensing container (ketchup bottle). Squirt directly onto painted surface. Using buffer pad, distribute compound with light pressure over the surface to be treated. Turn buffer on and, using medium pressure, work product for desired results. Can be applied with applicator pad and worked by hand on small area. Recommended for use with a wool cutting pad. **Not recommended for foam pads.**

SPECIFICATIONS

Appearance	Semi-Viscous Cream	Body Shop Safe - YES
Color	Light Brown	VOC Complaint - YES
Odor	Low Odor	Biodegradable - NO
Test	ASTM Method	Typical Results
Density, U.S. (lbs/gal) @ 77°F	D1475	~8.9
Solids, %	E1868	~20
Viscosity, Brookfield, cP		15,000

PACKAGING

Fill: 1 gal.

Case Quantity: 4

Case Weight: 39 lbs.